

ENERGY EFFICIENCY

Thermal Transmission Coefficient
 $U_w \geq 0.9$ (W/m²K)

Please consult typology, dimensions and glazing

ACCOUSTIC INSULATION

Maximum glazing: **55 mm**
 Maximum acoustic insulation: **Rw = 44 dB**

CATEGORIES ACHIEVED AT TEST CENTRE

Protection against atmospheric agents

Air permeability (EN 12207): **Class 4**
 Water tightness (EN 12208): **Class E1800**
 Wind resistance (EN 12210): **Class C5**

Reference test 1.23 x 1.48 m / 2 sashes.

Burglar resistance (EN 1627): **Grade RC2 (WK2)**

Reference test 2.52 x 1.47 m / 1 sash with EVO SECURITY hardware.

Security Test: **PAS24** **Passed**

Reference test: 1.100 x 2.400 mm / 1 Sash.

SECTIONS	Frame 70 mm Sash 78 mm
PROFILE THICKNESS	Window 1.5 mm Door 1.7 mm
MAXIMUM DIMENSIONS	Width (L) = 1.500 mm Height (H) = 2.600 mm
MAXIMUM WEIGHT/SASH	160 Kg

Please consult regarding maximum weight and dimensions according to types

FINISHES	<p>Colour powder coating (RAL, mottled, rough...) According to Qualicoat >60 microns</p> <p>Wood effect powder coating According to Qualideco standard</p> <p>Anodized According to Ewwa Euras Standard Class 15 Optionally Class 20 and 25 Optionally bicoloured</p>
HARDWARE	<p>Optionally concealed hinges</p> <p>Optionally security hardware</p>
AESTHETIC POSSIBILITIES	<p>Sash: Straight</p> <p>Bead: Straight or curved</p>

EXTRUSION ALLOY	6063 T-5
-----------------	----------

POLYAMIDE STRIP LENGTH	Polyamide 6.6 reinforced with 25% fiberglass: 32 to 35 mm
------------------------	--

GASKETS	EPDM triple gasket
---------	--------------------

FOAMS	Perimeter polyolefin foam in glazing rebate zone
-------	--

OPENING POSSIBILITIES	
INWARD	Side hung, tilt & turn, tilt & parallel, bottom hung
OUTWARD	Side hung, top hung, pivoting on horizontal or vertical axis

CERTIFICATES	
DTA certification from CSTB lab	
Certification - 3204	

